



Kraftsperrur eru settar saman með gaddaplötum, miðar er við 2KN/m² snjóðlag.

H.S.Á. TEIKNISTOFA

HARALDUR ÁRNASON - KT: 120149-2539 / HARA ehf. KT: 531101-2860
FURUVÖLLUM 13 - 600 AKUREYRI
SÍMI: 462-5777, 861-6616
FAX: 461-1852
e-mail: hara@hara.is

Haraldur Arnason

VERKHEITI				VERK NR 03-323	
HEITI TEIKNINGAR				TEIKNING NR 1708	
Kraftsperra T1-3 og T12.					
HANNAD	HÁ	TEIKNAD	HÁ	YFIRFARID	DAGS 16.06.2004
BREYTT	1		2	3	4
					5

Ath.
Sjá almennar skýringar á teikn. nr. 1700.
Undirstöður / sökklar - sjá teikn. nr. 1701.
Grunnmynd gólfbita - sjá teikn. nr. 1702.
Snið í undirst. og gólfbita - sjá teikn. nr. 1703.
Grunnmynd veggjagrinda - sjá teikn. nr. 1704.
Útlit veggjagrinda - sjá teikn. nr. 1705.
Grunnmynd þakviðar - sjá teikn. nr. 1706.
Sérmyndir í vegg og þak - sjá teikn. nr. 1707.
Kraftsperrur - sjá teikn. nr. 1707-10.